

TB-720

10-in-1 Touch Screen OTDR



SPECIFICATION

Model	TB-720-B	TB-720-M	TB-720-P1
Wavelength	1310/1550nm	850/1300nm	1310/1550/1625nm
Dynamic range	32/30dB	20/24dB	32/30/30dB
Distance setting	Max. 150km	Max. 40km	Max. 150km
Connector	SC/UPC interchangeable adapter or customize		SC/UPC or customize
Pulse width	5ns~20μs	5ns~1μs	5ns~20μs
Event dead zone	1m		
Attenuation dead zone	6m		
OLS function	Same wavelength and connector as OTDR		
OPM function	-50~+26dBm, 2.5mm universal connector 850,980,1270,1300, 1310, 1490, 1550,1577, 1625,1650nm		
VFL function	10mW, 2.5mm universal connector		
Storage	Internal memory or TF card(optional)		
Power & Data port	TYPE-C		
Power bank	Type-A 3.7V, 5000mAh		
Operation Temperature	0~+50°C, <90% RH		
Storage Temperature	-20~+70°C, <90% RH		
Size	160*85*38mm		
Weight	About 430g		

ACCESSORIES

STANDARD



Carrying Bag



Manual



Calibration Certificate



AC/DC Adapter
Type -C

OPTIONAL



FCU=FC/UPC
FCA=FC/APC



SCU=SC/UPC
SCA=SC/APC



SCU male-SCA female



LCU=LC/UPC



STU=ST/UPC



SCA male-SCU female

ORDERING INFORMATION

TB-720-B-SCA, 1310/1550nm, 32/30dB, OTDR SC/APC connector

TB-720-M-FCU, 850/1300nm, 20/24dB, OTDR FC/UPC connector

TB-720-P1-SCU-SCA, 1310/1550nm SC/UPC connector, 1625nm SC/APC connector